



**Electro Optical Components, Inc.**

5464 Skylane Boulevard, Suite D, Santa Rosa, CA 95403

Toll Free: 855-EOC-6300

[www.eoc-inc.com](http://www.eoc-inc.com) | [info@eoc-inc.com](mailto:info@eoc-inc.com)



# BLACK EYE

## MIR Hyperspectral Imaging Camera (2900 – 4200 nm)

The **BlackEye** is a linescan (pushbroom) mid-infrared (MIR) hyperspectral imaging camera that allows the acquisition of real-time data with high spatial and spectral resolution.

This high-sensitive and ultra-fast camera is an excellent solution even for the most challenging chemical imaging applications in laboratories and industrial manufacturing, for example, black plastic or mineral identification and sorting.

Based on superior transmission optical design with reflection grating technology, fast cryo-cooled InSb detector and high-end electronics, the **BlackEye** camera brings an exceptional performance even under harsh environmental conditions.

By choosing various camera lenses (fore optics), the **BlackEye** can be easily adapted to a wide range of applications, ensuring optimal image quality and size.

Moreover, different software packages are available for various demands: from software development kit up to the industrial software for the real-time measurements, analysis and process control.



### Features:

- Superior sensitivity and stability
- High frame rate
- Outstanding imaging performance
- Robust design without moving parts

## Technical Specifications:

### BlackEye

#### Spectrograph

Spectral range	typ. 2900 – 4200 nm
Dispersion	171 nm/mm
Spectral resolution	< 18 nm (with 80 µm slit)
Spatial resolution	rms spot radius < 40 µm
Smile	< 180 µm
Keystone	< 35 µm
F-number	4
Slit width, default	80µm (others on request)

#### Electronics

Sensor	InSb
Pixels in full frame	320 x 256
Pixel size	30 x 30 µm
Bit depth	14 bit
Frame rate	383 Hz @ integration time < 2.6 ms
Data interface	Gigabit Ethernet /CamLink
Power consumption	< 50W
Power supply	12 V/ 5 A DC
Cooling	Stirling cooling, MTBF 8000 h

#### Operating Conditions

Temperature (operating)	- 5 °C - + 40 °C
Temperature (storage)	-10 °C - + 50 °C

#### Mechanics

Dimensions l x w x h	436 x 184 x 258 mm
Weight	7 kg
Lens mount	Bayonet

As a well established manufacturer of spectroscopic measurement equipment, **inno-spec** provides optimized solutions for any individual applications: from customized OEM components for system suppliers up to fully integrated turnkey solutions for the end-customers.

## Accessories:

- Dedicated lighting solutions
- Various mounting accessories
- Different fore optics: 7 mm, 13 mm, 25 mm, 50 mm, 100 mm
- Conveyor belt or stepper table
- Several software packages