



**Electro Optical Components, Inc.**

5460 Skylane Boulevard, Santa Rosa, CA 95403

Toll Free: 855-EOC-6300


[www.eoc-inc.com](http://www.eoc-inc.com) | [info@eoc-inc.com](mailto:info@eoc-inc.com)



## 808nm 3W Narrow Linewidth Laser Diode Module

R808±0.5-3WF-R6-G

R808±0.5-4WW-CM-G



### Feature

Output power: 3W

Wavelength: 808±0.5nm

Fiber core: 105µm, 0.22NA



Free space output optional

### Application

Science

Laser pumping

## 808nm 3W Characteristics (25°C)



## Typical Device Performance(25°C)

Parameter		Symbol	Typical Value		Unit
			R808±0.5-3WF-R6-G	R808±0.5-4WW-CM-G	
Optical	CW Output Power	$P_{op}$	3	4	W
	Center Wavelength	$\lambda_c$	808±0.5		nm
	Spectral Width	$\Delta\lambda$	<0.5		nm
	Temperature drift of Wavelength	$\Delta\lambda / \Delta T$	0.01		nm/°C
Electrical	Threshold Current	$I_{th}$	0.64	0.65	A
	Operating Current	$I_{op}$	4.0	4.62	A
	Operating Voltage	$V_{op}$	1.9	1.92	V
	Slope Efficiency	$\eta_{es}$	0.9	1.0	W/A
	PD current	$I_{PD}$	<2000	-	μA
	Thermistor	$R_t$	10±5%/3450	-	kΩ/β(25°C)
Fiber	Fiber Core Diameter	$d_{core}$	105	-	μm
	Fiber Clad Diameter	$d_{clad}$	125	-	μm
	Fiber Buffer Diameter	$d_{buffer}$	250	-	μm
	Numerical Aperture	NA	0.22	-	-
	Connector	-	FC/PC,ST,SMA905	-	-

## Other Parameters

Parameter	Operating Temperature /°C	Operating Relative Humidity /%	Storage Temperature /°C	Storage Relative Humidity /%	Lead Soldering Temperature(max/°C)
Min	10	-	-20	-	-
Max	30	75	70	90	250(10Sec.)

## Package Dimensions (mm)

Pin	Function
1	Laser (+)
2	Laser (-)
3	Thermistor
4	Thermistor
5	PD(N)
6	PD(P)

