



FIBERPOINT® ET - Black

Fiber Optic Fault Locator - Made in Germany

(Part-Number: 1400000097Q / 1400000097)


The compact design of the visual fault locator is very suitable for daily use in all fiber optic applications e.g. in the field, in industrial environment as well as in laboratory.

APPLICATIONS

- To check singlemode/multimode optical fibers and other fiber optic components on faults.
- Patching of fibers.
- Continuity check up to ~ 5 km

FEATURES

- Private labelling is available at no extra cost.
- Minimum order quantity applies
- For resellers only



Parameter	Min.	Typ.	Max.
Wavelength	650 nm	650 nm	660 nm
Operation temperature	- 10 °C		45 °C
Storage temperature	- 40 °C		70 °C
Fiber coupled power: Singlemode fiber 9/125 µm Multimode fiber 50/125µm	200 µW 200 µW	350 µW 600 µW	
Optical output power			< 1 mW
Operation current		35 mA	
Retention force for ferrule		1 - 2 N	
Weight incl. batteries			56 g
Operation time - one battery pack ¹ (Pulsed mode)			40 hours
Battery type			AAA
Operation mode	continuous wave; pulsed mode: frequency 2 - 3 Hz		
Laser protection class			2 M
Suitable ferrule 2.5 mm			DIN, E2000, FC, SC, ST

INCLUDED IN DELIVERY

Dust cap, One battery pack (1 Battery: VARTA Industrial Alkaline No. 4003; 1.5 V; AAA), Instruction manual

ACCESSORIES (NOT INCLUDED)

Adapters for 1.25 mm ferrules (1400000070), POF (14000000078) and SMA (1400000088) are available

ORDER NUMBER

- 1400000097Q: Individually packed in Quadrosafe
- 1400000097: Individually packed in etui style plastic packaging

NOTES

Do not use rechargeable batteries. Compliant with RoHS-requirements (2011/65/EU from 08.06.2011). The above product specifications are subject to change without notice. Release 05/2016.