



## Product Data Sheet

**ELECTROCHEMICAL SO<sub>2</sub>-2000 SENSOR (3 SERIES) (P/N:056-3000-000)**

### • Description

The sensor is designed for the measurement of SO<sub>2</sub> concentration in gas phase. It can be used as the pin to pin replacement of the standard 3 series electrochemical SO<sub>2</sub> sensor.

### • Performance Characteristics

Nominal Range: 0~2000 ppm

Maximum Overload: 5000 ppm

Sensitivity(20 °C) : 0.10 ± 0.02 µA/ppm

Response Time (T90): ≤ 35 s

Zero Signal(20 °C) : ±2 ppm

Baseline Shift (-20 °C ~ 50 °C) : <5 ppm

Resolution: 1 ppm

Linearity: Linear up to 2000 ppm

Bias Voltage: 0 mV

### • Environmental

Temperature Range: -20 °C ~ 50 °C

Pressure Range: 1 atm ± 10 %

Humidity Range: 15 % ~ 90 %RH non-condensing

### • Life Time

Long Time Output Drift: < 2 % signal/month

Recommended Storage Temp: 10 °C ~ 30 °C

Expected Operating Life: 3 years in clean air

Storage Life: 6 months in original packaging

Warranty: 12 months

### • Intrinsic Safety Data

Maximum Current at 5000 ppm SO<sub>2</sub>: <1 mA

Maximum O/C Voltage: 1.3 V

Maximum S/C Current: <1.0 A

### • Physical Characteristics

Housing Material: ABS


Weight (Nominal): 23 g

Orientation: None

### • Installation

Output signals from the sensor pins are different. Inappropriate use of the pins in product design will affect the sensor functionality. Exposure to high concentrations of solvent vapors should be avoided under any condition. Mechanical overstress may cause deformation or cracks of the plastic enclosure of the sensor. If the sensor is used in extreme environmental conditions, please contact us if you need more details.

### Product Dimensions



All dimensions in mm

All tolerances ±0.15 mm unless otherwise stated

### Note

The performance data in this document is conducted by using SemeaTech recommended test circuitry and test environment at 20 °C, 50 %RH and 1 atm.


Sensor performance varies under different environmental conditions, please contact us if you need more details.

### • Cross-Sensitivity Data

Gas	Concentration (ppm)	Output signal (ppm SO <sub>2</sub> equivalent)
Nitrogen Dioxide	90	-84
Nitric Oxide	250	-2
Carbon Monoxide	500	4.7
Hydrogen	200	2.7
Hydrogen Chloride	100	0.2
Hydrogen Sulfide	200	-0.7
Ethylene	200	48

Note: The cross sensitivity are including but not limited to the above gases. It may also respond to other gases. The data in the table above may vary from different batches of sensors and the changes of test environment. Calibration with cross sensitivity gas is not recommended.

### • Temperature Data



### • Safety Note

The sensor is designed to be used in certain instruments for life critical applications. To ensure the sensor functioning per its specifications inside the instrument, it is required to read the instrument user's guide carefully and comply with the calibration procedures by using certified target calibration gas before each use. Failure to do so may cause serious injury and fatality. Please do not open the housing because the electrolyte stored inside is harmful.

It is highly recommended for customers to validate the sensor performance using this document as a reference for their product designs or applications.

This product data sheet is used for reference only.  
SemeaTech is committed to provide its customers the most accurate date based on its best knowledge.  
SemeaTech does not provide product warranty for failure to use its product in accordance with product specifications described in the data sheet, or other misuse, abuse, negligence to the product.