



Electro Optical Components, Inc.

5464 Skylane Boulevard, Suite D, Santa Rosa, CA 95403

Toll Free: 855-EOC-6300

www.eoc-inc.com | info@eoc-inc.com



PULSABLE IR SOURCE Model EP-3963*

Helioworks, Inc. offers a unique pulsable infrared emitter with a tungsten filament that provides mid IR radiation to over 5 microns. It operates in pulsed or steady state mode at temperatures in excess of 1900° K in an industry standard TO-8 package.

Key Features Include:

- Tungsten Filament
- Can Be Operated in Pulsed or Steady State Mode
- Internal Gold Plated Parabolic Reflector
- Sapphire Window
- Standard TO-8 Package




Electrical Specifications:

Peak Voltage = 3.0 Volts DC Maximum

Peak Current = 1.0 Amp


Peak Power = 3.0 Watts

Current vs Voltage




Modulation vs. Frequency

(50% Duty Cycle)



Radiant Exitance

Volts = 3.0, Distance = 3.0 inches from source



Polar Angle	Average (W/CM2)
-20	4.00E-03
-15	7.40E-03
-10	2.40E-02
-5	4.15E-02
0	4.55E-02
5	3.75E-02
10	2.15E-02
15	5.40E-03
20	3.70E-03